antibodies .- online.com





Datasheet for ABIN612590

Rabbit anti-Llama IgG (Heavy & Light Chain) Antibody (DyLight 350)



Go to Product page

0	1 /	0	K	/ 1	\sim	1 A /
	1//	\vdash	I \	71	\vdash	\/\/

Quantity:	1 mg		
Target:	IgG		
Binding Specificity:	Heavy & Light Chain		
Reactivity:	Llama		
Host:	Rabbit		
Conjugate:	DyLight 350		
Application:	Flow Cytometry (FACS), Immunofluorescence (IF)		
Product Details			
Immunogen:	Purified Ilama IgG, whole molecule		
Characteristics:	Rabbit anti-llama IgG (H&L) - Affinity Pure, DyLight 350 Conjugate.		
	Fluorphore: DyLight 350 (Ex = 353 nm, Em = 432 nm).		
	Fluor Protein Ratio: Moles DyLight 350 per Mole Antibody.		
Purification:	Affinity purified using solid phase mouse IgM (H&L)		
Purity:	> 95 % based on SDS-PAGE		
Target Details			
Target:	IgG		
Abstract:	IgG Products		
Target Type:	Antibody		

Application Details

Application Notes:	This conjugate is suitable for immunomicroscopy, flow cytometry.			
	The optimal working dilution should be determined by the investigator. Suggested starting			
	dilution: 1:20 - 1:2,000 for most applications			
Comment:	Country of Origin: Rabbit serum was obtained from healthy animals of US origin, under the care			
	of a registered veterinarian.			
	DyLight is a trademark of Thermo Fisher Scientific, Inc. and its subsidiaries.			
Restrictions:	For Research Use only			
Handling				
Format:	Lyophilized			
Concentration:	1.0 mg/mL			
Buffer:	10 mM Sodium Phosphate, 0.15 M Sodium Chloride, pH 7.2, 1 % (w/v) BSA, Protease/IgG free.			
	0.05 % (w/v) Sodium Azide			
Preservative:	Sodium azide			
Precaution of Use:	WARNING: Reagents contain sodium azide. Sodium azide is very toxic if ingested or inhaled.			
	Avoid contact with skin, eyes, or clothing. Wear eye or face protection when handling. If skin or			
	eye contact occurs, wash with copious amounts of water. If ingested or inhaled, contact a			
	physician immediately. Sodium azide yields toxic hydrazoic acid under acidic conditions. Dilute			
	azide-containing compounds in running water before discarding to avoid accumulation of			
	potentially explosive deposits in lead or copper plumbing.			
Storage:	4 °C			